ar	dno	er							
		env	er		COMPRES	SOR DATA SHE	ET		
			Fede				npressors Not Applie	cable	
Г					otary Compressor MODEL DATA - 1				l
-	1 Manufacturer: Gardner Denver								
-		Model Number TVS315-W155 (NA-IP55)				-IP55)	Date:	June 2024	
	2	Air-cooled X Water-cooled					Type:	C	
	2	Oil Injected X Oil-Free						~	
_							# of Stages:	2	
	3*	Full Load Operating Pressure <sup>b</sup>					100	psig <sup>b</sup>	
_	4	Drive Motor Nominal Rating					422	hp	
_	5	Drive Motor Nominal Efficiency					95.9%	percent	
_	6	Fan Motor Nominal Rating (if applicable)					2.4	hp	
	7	Fan Motor Nominal Efficiency					82.5%	percent	
		Input Power (kW)					Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>	
		<b>328.2</b> Max				Max	1809	18.14	
	0.1	272.3					1577	17.27	
	8*	222.0					1332	16.67	
		176.6					1076	16.42	
		135.3					810	16.71	
-		<b>97.4</b> Min				Min	536	18.19	
	9*	Total Package Input Power at Zero Flow <sup>c, d</sup>					0.0	kW	
	10	Specific Power (kW/100ACFM)	30.00 25.00 20.00						
	I		15.00						
			10.00	0 200	400 600	800 1000	1200 1400 1600	0 1800 2000	
		Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity							
L	* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator								I
	Consult C		e for a list TES:	a.	ACFM is actual cubic for	rge terminal point of the co feet per minute at inlet con	ompressor package in accordat ditions. I Electrical Consumption were		
U	5/					ordance with ISO 1217, A "not significant" or "0" or		load power equals less than 1%	
Comp	ressed /	Air & Gas I	nstitute	d.	Tolerance is specified in	-			
I	Member				NOTE: The terms "pow	ver" and "energy" are syno	nymous for purposes of this de	ocument	
						flow rate d conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Fle Power
					m <sup>3</sup> /min	ft <sup>3</sup> /min	Volume Flow Rate %	%	I UWCI
								+/-8	
					Below 0.5	Below 17.6	+/-7	17-0	
)31.2					Below 0.5 0.5 to 1.5 1.5 to 15	Below 17.6 17.6 to 53 53 to 529.7	+/-7 +/-6 +/-5	+/-7 +/-6	+/- 10%