## **Gardner Denver**

## COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

**Rotary Compressor: Variable Frequency Drive** MODEL DATA - FOR COMPRESSED AIR Manufacturer: Gardner Denver PureAir TVS90 Model Number Date June 2024 Air-cooled Water-cooled Type 2 Screw Oil Injected Oil-Free # of Stages 2 3\* Full Load Operating Pressure<sup>b</sup> 115 psigb 4 Drive Motor Nominal Rating 125 hp 5 Drive Motor Nominal Efficiency 94.8% percent Fan Motor Nominal Rating (if applicable) 1.2 6 hp Fan Motor Nominal Efficiency 82.5% percent Specific Power Input Power (kW) Capacity (acfm) a,d (kW/100 acfm)<sup>d</sup> 109.9 Max 595 18.48 97.6 528 18.49 8\* 85.6 460 18.62 391 18.94 74.0 321 19.55 62.7 51.8 250 20.74 0.0 kW Total Package Input Power at Zero Flow<sup>c, d</sup> 30 25 Specific Power (kW/100ACFM) 10 10 400 600 800 1000 1200 Capacity (ACFM)

\* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: NOTES

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity

- $b. \ \ The operating \ pressure \ at \ which \ the \ Capacity \ and \ Electrical \ Consumption \ were \ measured \ for \ this \ data \ sheet.$
- $^{\text{C.}}$  No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Volume flow rate Specific Energy No Load / Zero Flow Consumption at specified conditions Volume Flow Rate Power m<sup>3</sup>/min Below 0.5 Below 17.6 +/-8 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 53 to 529.7 1.5 to 15 +/-5 +/-6 Above 15 Above 529.7 +/-4 This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data



Member:

ROT 031.2

Member: