ar	dno	er							
		env	er		COMPRES	SOR DATA SHE	ET		
							npressors Not Applic	cable	
ſ						r: Variable Frequ FOR COMPRES			
Ī	1 Manufacturer: Gardner Denver						5.55		
		Model Number TVS200-A155 (NA-IP55)				IP55)	Date:	June 2024	
	2	X Air-cooled Water-cooled					Туре:	Screw	
_		Oil Injected X Oil-Free					# of Stages:	2	
	3*	Full Load Operating Pressure ^b					150	psig ^b	
	4	Drive Motor Nominal Rating					268	hp	
	5	Drive Motor Nominal Efficiency					94.9%	percent	
Ī	6	Fan Motor Nominal Rating (if applicable)					20.1	hp	
	7	Fan Motor Nominal Efficiency					92.1%	percent	
		Input Power (kW)					Capacity (acfm) a,d	Specific Power (kW/100 acfm) ^d	
		215.3 Max				Max	1016	21.19	
	8*	192.0					897	21.42	
		169.6					775	21.88	
		148.0					652	22.69	
	·	127.0					528	24.07	
		106.5 Min				Min	401	26.54	
	9*	Total Package Input Power at Zero Flow ^{c, d}					0.0	kW	
		Specific Power (kW/100ACEM)	35.00 30.00 25.00						
	10		20.00						
			15.00						
			10.00					1 1	
			(200	400 600	800 1000	1200 1400 1600	1800 2000	
		Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity							
L	* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator								I
	Consult C		for a list TES:	a.	ACFM is actual cubic f	ge terminal point of the co eet per minute at inlet con	ompressor package in accordar iditions. I Electrical Consumption were		
					No Load Power. In acco	ordance with ISO 1217, A	nnex E, if measurement of no	load power equals less than 1%	
Comp	ressed A	ir & Gas I	nstitute) d		"not significant" or "0" of ISO 1217, Annex E, as s			
							snown in table below: nymous for purposes of this do	ocument	
	Member					flow rate		Specific Energy	No Load / Zero Fl
					at specified	d conditions	Volume Flow Rate	Consumption	Power
					m ³ /min	ft ³ /min Palow 17.6	%	%	
					Below 0.5 0.5 to 1.5	Below 17.6 17.6 to 53	+/-7 +/-6	+/-8 +/-7	+/- 10%
21.2					1.5 to 15	53 to 529.7	+/-5	+/-6	10/0
31.2									