Gardner Denver

COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable

Rotary Compressor: Variable Frequency Drive MODEL DATA - FOR COMPRESSED AIR Manufacturer: Gardner Denver PureAir TVS160 Model Number Date June 2024 Air-cooled Water-cooled Type 2 Screw Oil-Free Oil Injected # of Stages 2 3* Full Load Operating Pressure^b 115 psigb 4 Drive Motor Nominal Rating 200 hp 5 Drive Motor Nominal Efficiency 95.3% percent Fan Motor Nominal Rating (if applicable) 1.2 6 hp Fan Motor Nominal Efficiency 82.5% percent Specific Power Input Power (kW) Capacity (acfm) a,d (kW/100 acfm)^d 171.1 Max 898 19.05 145.7 **781** 18.66 8* 18.38 120.9 658 531 97.3 18.31 400 74.8 18.69 53.7 266 20.21 0.0 kW Total Package Input Power at Zero Flow^{c, d} 30 25 Specific Power (kW/100ACFM) 10 10 400 600 800 1000 1200

* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: NOTES

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with

ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

- $b. \ \ The operating \ pressure \ at \ which \ the \ Capacity \ and \ Electrical \ Consumption \ were \ measured \ for \ this \ data \ sheet.$
- $^{\text{C.}}$ No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Volume flow rate Specific Energy No Load / Zero Flow Consumption at specified conditions Volume Flow Rate Power m³/min Below 0.5 Below 17.6 +/-8 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 53 to 529.7 1.5 to 15 +/-5 +/-6 Above 15 Above 529.7 +/-4 This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data



Member:

Member:

ROT 031.2