ar	dno	er							
		env	er		COMPRES	SOR DATA SHE	ET		
			Fed				npressors Not Applie	cable	
Г					otary Compresson MODEL DATA -				
Ī	1 Manufacturer: Gardner Denver								
Ē		Model Number TVS355-W155 (NA-IP23)				·IP23)	Date:	June 2024	
	2	Air-cooled X Water-cooled					Type:	Screw	
	2				-			~	
Ļ		Oil Injected X Oil-Free					# of Stages:		
ŀ	3*	Full Load Operating Pressure ^b					100	psig ^b	
-	4	Drive Motor Nominal Rating					476	hp	
-	5	Drive Motor Nominal Efficiency					95.7%	percent	
-	6	Fan Motor Nominal Rating (if applicable)					2.4	hp	
_	7	Fan Motor Nominal Efficiency					82.5%	percent	
		Input Power (kW)					Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
				329.1		Max	1809	18.19	
	8*	275.0					1577	17.44	
		225.1					1332	16.90	
		179.1					1076	16.65	
-		136.8					810	16.90	
						Min	536	18.28	
	9*	Total Package Input Power at Zero Flow ^{c, d}					0.0	kW	
			35.00						
			55.00						
			30.00						
		Specific Power (kW/100ACFM)							
			25.00						
			20.00						
	10								
			15.00						
			10.00						
				0 200	400 600	800 1000	1200 1400 1600	0 1800 2000	
		Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35							
			X-Axis Scale, 0 to 25% over maximum capacity						
	* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator								
(Consult C		for a list TES:		in the third party verif		ompressor package in accordat	www.cagi.org ace with ISO 1217, Annex E;	
					ACFM is actual cubic f	eet per minute at inlet con	ditions.		
Г							Electrical Consumption were nnex E, if measurement of no	measured for this data sheet. load power equals less than 1%	
Comp	ressed A	ir & Gas I	nstitute			"not significant" or "0" or	n the test report.		
					-		nymous for purposes of this de	ocument	
1	Member				Volume	flow rate		Specific Energy	No Load / Zero Fl
						t conditions ft ³ /min	Volume Flow Rate	Consumption	Power
					m /min Below 0.5	nt /min Below 17.6	% +/-7	% +/-8	
					0.5 to 1.5	17.6 to 53	+/-6	+/-7	+/- 10%
031.2					1.5 to 15 Above 15	53 to 529.7 Above 529.7	+/-5 +/-4	+/-6 +/-5	