Gardner

Denver
Federal Uniform Test Method for Certain Air Compressors Not Applicable
Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Gardner Denver		
	Model Number PureAir TVS110	Date:	June 2024
2	X Air-cooled Water-cooled	Туре:	Screw
	Oil Injected X Oil-Free	# of Stages:	2
3*	Full Load Operating Pressure ^b	115	psig ^b
4	Drive Motor Nominal Rating	150	hp
5	Drive Motor Nominal Efficiency	94.9%	percent
6	Fan Motor Nominal Rating (if applicable)	10.1	hp
7	Fan Motor Nominal Efficiency	92.1%	percent
8*	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) ^d
	128.6 Max	684	18.81
	111.9	600	18.63
	95.7	515	18.58
	80.3	428	18.74
	65.5	340	19.27
	51.3 Min	250	20.55
9*	Total Package Input Power at Zero Flow ^{c, d}	0.0	kW
10	30 Specific Power (kW/100ACFM) 20 12 12 12 12 12 12 12 12 12 12 12 12 12		1000
	0 200 400 600	800	1000 1200
	Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity		

* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

 $Consult\ CAGI\ website\ for\ a\ list\ of\ participants\ in\ the\ third\ party\ verification\ program:$

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with

ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions. $b. \ \ The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.$

- $^{\text{C.}}$ No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Specific Energy Consumption No Load / Zero Flow Power at specified conditions Volume Flow Rate m³/min Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 1.5 to 15 53 to 529.7 +/-5 +/-6 Above 15 Above 529.7



Member:

Member:

ROT 031.2

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data