ar	dno	er							
		env	er		COMPRES	SOR DATA SHE	ET		
							npressors Not Applie	cable	
Г					otary Compressor MODEL DATA - 1]
Ī	1 Manufacturer: Gardner Denver								
Ī		Model Number TVS200-W155 (NA-IP55)				-IP55)	Date:	June 2024	
	2	Air-cooled X Water-cooled					Type:	Screw	
	2							~	
		Oil Injected X Oil-Free					# of Stages:		
-	3*	Full Load Operating Pressure ^b					125	psig ^b	
	4	Drive Motor Nominal Rating					268	hp	
	5	Drive Motor Nominal Efficiency					94.9%	percent	
	6	Fan Motor Nominal Rating (if applicable)					2.4	hp	
	7	Fan Motor Nominal Efficiency					82.5%	percent	
		Input Power (kW)					Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
		219.7 Max				Max	1178	18.65	
	0*	192.6					1033	18.65	
	8*	166.8					884	18.87	
		142.0					733	19.39	
		118.3					579	20.43	
-			95.3 Min				423	22.51	
	9*	Total Package Input Power at Zero Flow ^{c, d}					0.0	kW	
		Specific Power (kW/100ACFM)	30.00 25.00 20.00						
	10	Sp (kW					_		
			15.00						
			10.00	0 200	400 600	800 1000	1200 1400 1600	0 1800 2000	
		Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity							
	* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator								l
,	Consult C		for a list TES:	a.	ACFM is actual cubic for	rge terminal point of the co feet per minute at inlet con	ompressor package in accordar ditions. I Electrical Consumption were		
				c.		ordance with ISO 1217, A "not significant" or "0" or		load power equals less than 1%	
Comp	ressed A	Air & Gas I	nstitute	d.	Tolerance is specified in	-			
,	Member				NOTE: The terms "pow	ver" and "energy" are syno	nymous for purposes of this de	ocument	
1	wichit/Cl					flow rate	Volume Flore Data	Specific Energy	No Load / Zero Fle
					at specified m ³ /min	d conditions ft ³ /min	Volume Flow Rate %	Consumption %	Power
					Below 0.5	Below 17.6	+/-7	+/-8	1
					Below 0.5				
31.2					0.5 to 1.5 1.5 to 15	17.6 to 53 53 to 529.7	+/-6 +/-5	+/-7 +/-6	+/- 10%