ar	dne	er							
		env	er		COMPRES	SOR DATA SHE	ET		
							npressors Not Applic	cable	
1						r: Variable Frequ FOR COMPRES			
	1 Manufacturer: Gardner Denver								
		Model Number TVS355-W155 (NA-IP55)				-IP55)	Date:	June 2024	
	2	Air-cooled X Water-cooled					Type:	Screw	
		Oil Injected X Oil-Free					# of Stages:	2	
	3*	Full Load Operating Pressure <sup>b</sup>					115	psig <sup>b</sup>	
	4	Drive Motor Nominal Rating					476	hp	
	5	Drive Motor Nominal Efficiency					96.0%	percent	
	6	Fan Motor Nominal Rating (if applicable)					2.4	hp	
	7	Fan Motor Nominal Efficiency					82.5%	percent	
	8*	Input Power (kW)					Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>	
		345.2 Max				Max	1808	19.09	
		287.6					1576	18.25	
		235.5					1331	17.69	
		188.1					1074	17.51	
		144.8					808	17.92	
						Min	533	19.65	
	9*	Total Package Input Power at Zero Flow <sup>c, d</sup>					0.0	kW	
		Specific Power (kW/100A.CFM)	30.00 25.00						
	10		20.00						
	10								
			15.00						
			10.00			1 1		<u>,                                </u>	
				0 200	400 600	800 1000	1200 1400 1600	1800 2000	
		Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity							
l	* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator								I
	Consult C.		for a list TES:	a.	ACFM is actual cubic for	rge terminal point of the co feet per minute at inlet con	ompressor package in accordar ditions. I Electrical Consumption were		
					• No Load Power. In acco	ordance with ISO 1217, A	nnex E, if measurement of no	load power equals less than 1%	
Comp	pressed A	ir & Gas I	nstitute	d.	-	"not significant" or "0" or n ISO 1217, Annex E, as s			
							nymous for purposes of this de	ocument	
	Member				Volume	flow rate		Specific Energy	No Load / Zero Fl
					at specified	d conditions	Volume Flow Rate	Consumption	Power
					m <sup>3</sup> /min Below 0.5	ft <sup>3</sup> /min Below 17.6	%	%	
					0.5 to 1.5	Below 17.6 17.6 to 53	+/-/ +/-6	+/-8 +/-7	+/- 10%
									., 10/0
031.2					1.5 to 15	53 to 529.7	+/-5	+/-6	