## **Gardner** Denver

## COMPRESSOR DATA SHEET

Federal Uniform Test Method for Certain Air Compressors Not Applicable **Rotary Compressor: Variable Frequency Drive** 

	MODEL DATA - FOR COMPRES		
1	Manufacturer: Gardner Denver		
	Model Number PureAir TVS160	Date:	June 2024
2	X Air-cooled Water-cooled	Туре:	Screw
	Oil Injected X Oil-Free	# of Stages:	2
3*	Full Load Operating Pressure <sup>b</sup>	115	psig <sup>b</sup>
4	Drive Motor Nominal Rating	200	hp
5	Drive Motor Nominal Efficiency	95.3%	percent
6	Fan Motor Nominal Rating (if applicable)	10.1	hp
7	Fan Motor Nominal Efficiency	92.1%	percent
	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>
	174.8 Max	898	19.47
	147.9	780	18.96
8*	122.1	658	18.56
	97.7	531	18.40
	74.7	400	18.67
	<b>53.3</b> Min	266	20.04
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	0.0	kW
10	25 (kW/1000CFM) 15 10		
	0 200 400 600  Capacity (ACFM)  Note: Graph is only a visual representation of t  Note: Y-axis scale 10 to 35, +5kW/100acfm increme  X-Axis Scale, 0 to 25% over maximu	ents if necessary above 35	1000 1200

\* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program: NOTES:

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

- $b. \ \ The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.$
- $^{\text{C.}}$  No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Specific Energy Consumption No Load / Zero Flow Power at specified conditions Volume Flow Rate m<sup>3</sup>/min Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 1.5 to 15 53 to 529.7 +/-5 +/-6 Above 15 Above 529.7

Member:

ROT 031.2

Member:

Compressed Air & Gas Institute

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data