Gardner

Denver
Federal Uniform Test Method for Certain Air Compressors Not Applicable
Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Gardner Denver		
	Model Number PureAir TVS132	Date:	June 2024
2	Air-cooled X Water-cooled	Type:	Screw
	Oil Injected X Oil-Free	# of Stages:	2
3*	Full Load Operating Pressure ^b	150	psig ^b
4	Drive Motor Nominal Rating	175	hp
5	Drive Motor Nominal Efficiency	95.4%	percent
6	Fan Motor Nominal Rating (if applicable)	1.2	hp
7	Fan Motor Nominal Efficiency	82.5%	percent
8*	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) ^d
	161.5 Max	772	20.94
	140.4	675	20.80
	119.9	576	20.81
	99.9	474	21.09
	80.7	370	21.84
	62.3 Min	264	23.65
9*	Total Package Input Power at Zero Flow ^{c, d}	0.0	kW
10	30 25 (kw/1000GEW) 15 10 0 200 400 600	800	1000 1200
	Capacity (ACFM) Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity		

* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

Consult CAGI website for a list of participants in the third party verification program:

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

- $b. \ \ The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.$
- $^{\text{C.}}$ No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Specific Energy Consumption No Load / Zero Flow Volume flow rate Power at specified conditions Volume Flow Rate m³/min Below 0.5 Below 17.6 +/-8 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 1.5 to 15 53 to 529.7 +/-5 +/-6 Above 15 Above 529.7

Member:

ROT 031.2

Member:

Compressed Air & Gas Institute

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data