## **Gardner**

Denver
Federal Uniform Test Method for Certain Air Compressors Not Applicable
Compressor: Variable Frequency Drive

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Gardner Denver		
	Model Number PureAir TVS90	Date:	June 2024
2	Air-cooled X Water-cooled	Туре:	Screw
	Oil Injected X Oil-Free	# of Stages:	2
3*	Full Load Operating Pressure <sup>b</sup>	150	psig <sup>b</sup>
4	Drive Motor Nominal Rating	125	hp
5	Drive Motor Nominal Efficiency	94.8%	percent
6	Fan Motor Nominal Rating (if applicable)	1.2	hp
7	Fan Motor Nominal Efficiency	82.5%	percent
8*	Input Power (kW)	Capacity (acfm) a,d	Specific Power (kW/100 acfm) <sup>d</sup>
	<b>109.4</b> Ma	x 517	21.17
	101.6	477	21.31
	93.9	436	21.53
	86.3	395	21.84
	78.8	354	22.27
	<b>71.4</b> Mi	n 312	22.88
9*	Total Package Input Power at Zero Flow <sup>c, d</sup>	0.0	kW
10	30 Specific Power (kw/100ACFM) 20 20 15 15 10 10		
	0 200 400 600	800	1000 1200
	Capacity (ACFM)  Note: Graph is only a visual representation of the data in section 8  Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35  X-Axis Scale, 0 to 25% over maximum capacity		

\* For models that are tested in the CAGI Performance verification Program, these items are verified by program administrator

 $Consult\ CAGI\ website\ for\ a\ list\ of\ participants\ in\ the\ third\ party\ verification\ program:$ 

www.cagi.org

a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfm is actual cubic feet per minute at inlet conditions.

 $b. \ \ The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.$ 

 $^{\text{C.}}$  No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1% manufacturer may state "not significant" or "0" on the test report.

d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document

Specific Energy Consumption No Load / Zero Flow Power at specified conditions Volume Flow Rate m<sup>3</sup>/min Below 0.5 Below 17.6 0.5 to 1.5 17.6 to 53 +/-6 +/-7 +/- 10% 1.5 to 15 53 to 529.7 +/-5 +/-6 Above 15 Above 529.7

Member:

Member:

ROT 031.2

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data