| rc | ane | er | | | | | | | |
|------|----------|--|------------|---------------|--------------------------|--|--|--------------------------------|-------------------------|
| | | env | er | | COMPRES | SOR DATA SHE | ET | | |
| | | | | | | | npressors Not Applic | cable | |
| | | | | | | r: Variable Frequ FOR COMPRES | | | |
| | 1 | Manufacturer: Gardner Denver | | | | | | | |
| | | Model Number TVS250-W155 (NA-IP55) | | | | -IP55) | Date: | June 2024 | |
| | 2 | Air-cooled X Water | | | Water-cooled | | Type: | Screw | |
| | | | l Injecte | | Oil-Free | | # of Stages: | | |
| | 3* | Full Load Operating Pressure ^b | | | | | 115 | psig ^b | |
| | 4 | Drive Motor Nominal Rating | | | | | 335 | hp | |
| | 5 | Drive Motor Nominal Efficiency | | | | | 96.1% | percent | |
| | 6 | Fan Motor Nominal Rating (if applicable) | | | | | 2.4 | hp | |
| | 7 | Fan Motor Nominal Efficiency | | | | | 82.5% | percent | |
| - | | · · · · · · · · · · · · · · · · · · · | | | | | | Specific Power (kW/100 | |
| | | Input Power (kW) | | | | | Capacity (acfm) a,d | acfm) ^d | |
| | | | | 269.8 | | Max | 1494 | 18.06 | |
| | | 229.6 | | | | | 1298 | 17.69 | |
| | 8* | 192.5 | | | | | 1095 | 17.58 | |
| | | 158.1 | | | | | 886 | 17.84 | |
| | | 125.9 | | | | | 672 | 18.73 | |
| | | 95.3 Min | | | | Min | 453 | 21.03 | |
| | 9* | Total Package Input Power at Zero Flow ^{c, d} | | | | | 0.0 | kW | |
| | | | 35.00 | | | | | | |
| | | Specific Power (kW/100ACFM) | 30.00 | | | | | | |
| | | | 25.00 | | | | | | |
| | | | | | | | | | |
| | 10 | | 20.00 | | | | | | |
| | | | 15.00 | | | | | | |
| | | | | | | | | | |
| | | | 10.00 | 0 200 | 400 600 | 800 1000 | 1200 1400 1600 |) 1800 2000 | |
| | | | | | Capacity (ACFM) | | | | |
| | | Note: Graph is only a visual representation of the data in section 8 Note: Y-axis scale 10 to 35, +5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity | | | | | | | |
| | | | | | | | | | |
| * | For mode | els that are t | ested in t | he CAGI Perfo | rmance verification Pr | ogram, these items are | verified by program admin | nistrator | |
| | | | | | in the third party verif | - | JI G | www.cagi.org | |
| | | NO | TES: | a. | | rge terminal point of the co feet per minute at inlet con | ompressor package in accordar aditions. | ace with ISO 1217, Annex E; | |
| | | | | | · The operating pressure | at which the Capacity and | d Electrical Consumption were | | |
| L | | | | | | ordance with ISO 1217, A e "not significant" or "0" or | | load power equals less than 1% | |
| mpre | essed A | ir & Gas I | nstitute | ! d. | | n ISO 1217, Annex E, as s | | | |
| М | lember | | | | NOTE: The terms "pow | /er" and "energy" are syno | onymous for purposes of this de | | |
| | | | | | | e flow rate ed conditions | Volume Flow Rate | Specific Energy Consumption | No Load / Zero Power |
| | | | | | m ³ /min | ft ³ /min | % | % | |
| | | | | | Below 0.5 | Below 17.6 | +/-7 | +/-8 | |
| | | | | | | | 1 | | |
| .2 | | | | | 0.5 to 1.5 1.5 to 15 | 17.6 to 53 53 to 529.7 | +/-6 +/-5 | +/-7 +/-6 | +/- 10% |