



30-40 HP FIXED SPEED ROTARY SCREW COMPRESSORS

L-Series

Advanced Technology. Inspired Simplicity.

L-Series compressors from Gardner Denver feature more than just the latest compressor technology. They contain the cleanest, simplest, most intuitive machine layouts on the market. Equipped with standard TEFC main motors, wye-delta starters, GD Governor™ microprocessor controllers and quiet enclosures, an L-Series unit from Gardner Denver is the optimal solution when a feature-rich, simple-to-operate compressor is required.

First Class Serviceability

The L-Series units set a new standard in serviceability. By utilizing integrated airend design techniques, Gardner Denver delivers unprecedented access to service and routine maintenance items. At the same time, the compact design eliminates unneeded connections and minimizes piping; reducing the opportunity for leaks. Couple these features with an intuitive controller and you have a world class small horsepower compressor package.

Gardner
Denver

L23-L29 ROTARY SCREW COMPRESSOR

MODEL	DRIVE MOTOR		50 Hz				60 Hz				NOISE LEVEL ²		WEIGHT		DIMENSIONS L x W x H IN. (MM)
	HP	KW	NOMINAL PRESSURE		FAD ¹		NOMINAL PRESSURE		FAD ¹		DB(A)	LBS	KG		
			PSIG	BAR	ACFM	M ³ /MIN	PSIG	BAR	ACFM	M ³ /MIN					
L23	30	22	110	7.5	146.9	4.16	100	7.5	148.7	4.21	68	1433	650		
			145	10.0	121.8	3.45	125	10	125.0	3.54					
			190	13.0	105.2	2.98	190	13	100.6	2.85					
L26	35	26	110	7.5	170.9	4.84	100	7.5	172.8	4.89	69	1493	677	53.0 x 34.6 x 63.5 (1345 x 880 x 1612)	
			145	10.0	145.8	4.13	125	10	148.1	4.19					
			190	13.0	121.5	3.44	190	13	125.7	3.56					
L29	40	30	110	7.5	194.9	5.52	100	7.5	193.1	5.47	71	1501	681		
			145	10.0	169.9	4.81	125	10	173.0	4.90					
			190	13.0	145.5	4.12	190	13	147.4	4.17					

1) Data measured and stated in accordance with ISO1217, Ed. 4, Annex C & Annex E at the following conditions:

Air Intake Pressure 1 bar A, Air Intake Temperature 20° C, Humidity 0% (Dry)

2) Measured in free field conditions in accordance with ISO 2151, tolerance +/- 3 dB

L-Series Features (30-40 HP)

- Direct-gear drive, oil flooded, single stage rotary screw air compressor
- AEON 4000 lubricant
- Air-cooled only
- Air supply piping includes hard pipe design with Viton Victaulic couplings
- CRN and ASME rated aftercooler
- Electrical components UL Listed for the US and Canada, including C-UL-US listed open control panel
- Multi-compressor sequencing
- Built-in data logging
- GD Governor™ microprocessor controller
- Integrated spin-on oil filter
- Integrated thermostatic thermal mixing valve
- Type 1 electrical enclosure
- Load/no load control and timed shutdown
- iConn integrated
- Moisture separator (shipped loose)
- Mounted and wired wye-delta starter
- Quiet enclosure
- Second pressure band control for lead/lag operation
- TEFC main motor
- Two-stage air filter and air/oil separation system
- Voltage:
 - 230V/380V/460V/575V, 60 Hz
 - 230V/400V, 50 Hz (3 phase only)

Gardner Denver®

Gardner Denver, Inc.

1800 Gardner Expressway
Quincy, IL 62305
866-440-6241

www.gardnerdenverproducts.com



©2020 Gardner Denver, Inc. Printed in U.S.A.
GSCS-L23-L29 3rd Ed. 2/20

Please recycle after use.